

**WAVEGUIDE DEHYDRATOR TYPE 6250MKII
SHIP MOUNT DEHYDRATOR**



- ✓ DRY AIR TO BETTER THAN -40 CELSIUS
- ✓ LOW NOISE LEVELS & MINIMUM VIBRATION
- ✓ DIGITALLY CONTROLLED ALARMS
- ✓ WET AIR BY-PASS FAIL SAFE
- ✓ OIL-LESS AIR COMPRESSOR



BORROWMEADOW ROAD
SPRINGEKERSE ESTATE
STIRLING, FK7 7UW
SCOTLAND UK

TEL: +44 (0) 1786 449292
FAX: +44 (0) 1786 449393

WEB: WWW.CABLEPRESSURE.CO.UK

**WAVEGUIDE DEHYDRATOR TYPE 6250MKII
SHIP MOUNT DEHYDRATOR**

SPECIFICATIONS

COMPRESSOR	OIL-LESS AIR COMPRESSOR
POWER SUPPLY	110/115 VAC 60HZ
DRY AIR OUTPUT	FREE AIR DELIVERY 25 LTRS PER MIN
OUTPUT PRESSURE	FACTORY PRESET TO CUSTOMERS REQUIREMENTS
DEWPOINT	BETTER THAN -40 DEGREES CELSIUS
WET DRY BYPASS	FAIL SAFE SOLENOID VALVE CONTROLLED BY HUMIDITY DETECTOR
DISPLAY & ALARMS	COMPRESSOR TOTAL RUNNING HOURS OUTPUT DEWPOINT (LED) OUTPUT PRESSURE (LED) DEWPOINT & PRESSURE DISPLAY POWER ON/OFF LOWOUTPUT PRESSURE ALARM HIGH HUMIDITY ALARM MAINSFAIL ALARM
AIR DRIER	AUTOMATIC HEATLESS REACTIVATION DESICCANT
OPERATION	TEMPERATURE LIMITS OF +5 TO +40 DEGREES CELSIUS
DIMENSIONS	HEIGHT 600MM, WIDTH 500MM, DEPTH 300MM
PAINT FINISH	LIGHT ADMIRALTY GREY BS381c TINT 697 SEMI GLOSS